



- √ single bearing system
- √ stainless steel internal parts
- √ corrosion resistant
- √ easy rotation under maximum pressure
- ✓ reinforced inner shaft and bearings
- √ maintenance free

### Flow / Durchfluss






# swiss quality

MOSMATIC AG CH-9126 Necker | Phone: +41 (0)71 375 64 64 | www.mosmatic.com

## Most popular gun swivel

LIVE rotation even under pressures up to 275 bar. True stainless steel self lubricating bearing and supported inner shaft make a perfect fit for side load applications. Eliminates wrist fatigue, by eliminating the twisting of the hose, you will also prolong the life of your hoses, fittings and other connections. Maintenance free, no grease required and with over 50 thread configurations we have a model to fit your needs.

Application: HP-Guns, hose connections, hydraulics, tangle-free applications



## **DGV** (Additional configurations available)

•		_						
Part No.	G1 (M)	G2 (F)	NW	SW1	SW2	L1	L2	Weight
32.512	G1/4" M	G1/4" F	6	24	19	63	10	140g
32.514	G1/4" M	G3/8" F	6	24	22	64	10	160g
32.532	G3/8" M	G1/4" F	6	24	19	63	10	150g
32.534	G3/8" M	G3/8" F	6	24	22	64	10	170g

..M = male, F = female, G = gas pipe thread, NW = nominal width, SW = wrech size

#### **TECHNICAL DATA**

Pressure 275 bar
Temperature 120°C
RPM max. 30 rpm
Body stainless steel
brass, nickel plated

Inner part Seal Bearing stainless steel O-ring

1x thrust ball bearing

Throughput medium pH 3 - 12



