

SERIE SERIES SÉRIE SERIE SERIE	RACCORDO PORT SIZE RACCORD ANSCHLUSS ROSCA	PASSAGGIO ORIFICE PASSAGE NENNWEITE ORIFICIO	Kv	PRESSIONE DIFFERENZIALE DIFFERENTIAL PRESSURE PRESSION DIFFÉRENTIELLE DRUCKBEREICH PRESIÓN DIFERENCIAL			POTENZA NOMINALE NOMINAL POWER PUISSANCE NOMINALE LEISTUNGS-AUFNAHME POTENCIA NOMINAL			TENUTE SEALS ETANCHEITES DICHTUNGEN CIERRES	CAMPO DI TEMPERATURA TEMPERATURE RANGE GAMME DE TEMPÉRATURE TEMPERATURBEREICH TEMPERATURA TRABAJO	BOBINA COIL BOBINE SPULE BOBINA	FIG.	OPZIONI OPTIONS OPTIONS OPTIONEN OPCIONES
				Δp bar			AC ~ VA							
	G (ISO 228)	mm	m³/h	MIN	MAX		SPUNTO INRUSH APPEL ANZUG PUNTA	REGIME HOLD SERVICE BETRIEB SERVICIO	DC ---				TAGLIA SIZE TAILLE GRÖSSE TALLA	SERIE SERIES SÉRIE REIHE SERIE
					AC ~	DC ---			W		°C			

2/2


Servoazionata a membrana normalmente chiusa

Diaphragm servoassisted normally closed

Servopilotée a membrane normalement fermée

Servogesteuerte Membrane stromlos geschlossen

Servo pilotada por membrana normalmente cerrada



107	1/4"	10	1,5	0,15	15	15	12	8	6,5				22	3	1	1-5-7
	3/8"	10	1,7	0,15	15	15	12	8	6,5							
	3/8"	12	2,2	0,15	15	15	12	8	6,5	NBR	-10 +90					
	1/2"	12	2,5	0,15	15	15	12	8	6,5	EPDM	<+140					
	3/4"	18	5,5	0,15	13	13	12	8	6,5	FPM	-10 +130					
	1"	24	10,2	0,15	10	10	12	8	6,5							
	1 1/4"	30	15	0,15	10	10	12	8	6,5						2	
107	1 1/4"	37	18	0,15	10	10	20	15	10	NBR	-10 +90		30	2	3	1-5-7
	1 1/2"	37	21	0,15	10	10	20	15	10	EPDM	<+140					
	2"	50	36	0,15	10	10	20	15	10	FPM	-10 +130					
	2 1/2"	75	75	0,3	5	5	20	15	10	NBR	-10 +90					
	3"	75	84	0,3	5	5	20	15	10							
107W	3/8"	12	2,2	0,5	25	25	15	11	5				30	4	1	1-5-7
	1/2"	12	2,5	0,5	25	25	15	11	5							
	2 1/2"	75	75	3	15	15	20	15	10	NBR	-10 +90					
	3"	75	84	3	15	15	20	15	10							
177	3/8"	12	2,2	0,15	15	15	12	8	6,5	NBR	-10 +90		22	3	4	6
	1/2"	12	2,5	0,15	15	15	12	8	6,5	EPDM	<+140					
	3/4"	18	5,5	0,15	13	13	12	8	6,5	FPM	-10 +130					
	1"	24	10,2	0,15	10	10	12	8	6,5							

2/2


Servoazionata a pistone normalmente chiusa

Piston servoassisted normally closed

Servopilotée commandée par piston normalement fermée

servogesteuerte Kolbenventile stromlos geschlossen

Servo pilotada por pistón normalmente cerrada



119	1/4"	5,2	0,47	1,5	50	50	20	15	10				30	2	6	7
	3/8"	12	2	1	30	30	20	15	10							
	1/2"	12	2,2	1	30	30	20	15	10	PTFE	-10 +130					
	3/8"	12	2	1	50	50	40	30	27							
	1/2"	12	2,2	1	50	50	40	30	27							

FIG. 2

FIG. 4

FIG. 3

FIG. 1

FIG. 5

FIG. 6

